ANAEROBIC SEALANT

Medium resistance (removable)

Product informations

Medium-strength anaerobic sealant for metal joints, it can also be used to replace hemp, P.T.F.E. and gaskets; after being applied it forms an elastic film which guarantees a perfect seal against gas, compressed air, water. hydrocarbons, LPG, oils and many chemical products including refrigerant gases and allows easy assembly, even after some time.

Product features

- good wettability, combined with gap filling capacity (thixotropic)
- intermediate fixing

NB. To seal PVC, PP or Nylon fittings, ***use only P.T.F.E. based sealant*** (*SKU 50950 / 50951*) by ***pre-treating*** the plastic threads with ***the activator*** (*SKU 50959*), ***screw and tighten within 1 minute*** (longer waiting times can break the sealant film that is already forming. ***Do not use the thread sealer*** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

Technical Features

MAX Ø FOR USE 2" - CLEARANCE 0,3 MM	
COLOUR	BLUE
DETECTION	FLUORESCENT IN BLUE LIGHT

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Anaerobic Sealant

FLASH POINT	> + 100°C
MANIPULATION	15 - 30 MINUTES
HARDENING TIME	1 - 3 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 180°C

SKU	MODEL	PRICE
00000050952	ANAEROBIC SEALANT 15-36 - 75 ML	€17.55 VAT EXCLUDED
00000050953	ANAEROBIC SEALANT 15-36 - 250 ML	€48.95 VAT EXCLUDED



Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net