



Catalogues and Products > Heating > Sealants and Sealing Accessories > **Anaerobic Sealant**

ANAEROBIC SEALANT

Medium resistance (removable)

Product informations

Medium-strength anaerobic sealant for metal joints, it can also be used to replace hemp, P.T.F.E. and gaskets; after being applied it forms an elastic film which guarantees a perfect seal against gas, compressed air, water, hydrocarbons, LPG, oils and many chemical products including refrigerant gases and allows easy assembly, even after some time.

Product features

- good wettability, combined with gap filling capacity (thixotropic)
- intermediate fixing

NB. To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming). **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

Technical Features

MAX Ø FOR USE 2" - CLEARANCE 0,3 MM	
COLOUR	BLUE
DETECTION	FLUORESCENT IN BLUE LIGHT



Anaerobic Sealant

FLASH POINT	> + 100°C
MANIPULATION	15 - 30 MINUTES
HARDENING TIME	1 - 3 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 180°C

SKU	MODEL	PRICE
00000050952	ANAEROBIC SEALANT 15-36 - 75 ML	€17.55 VAT EXCLUDED
00000050953	ANAEROBIC SEALANT 15-36 - 250 ML	€48.95 VAT EXCLUDED

