



Catalogues and Products > Air-Conditioning > Brackets > **Anchor**

ANCHOR

With hex head screw

Product informations

Universal anchor for fastenings on all types of masonry, plasterboard and concrete.

Product features

- particularly suitable in perforated and hollow walls
- thanks to its special shaping, allows expansion in 6 different directions for consistently effective anchorages on all types of masonry
- equipped with a dynamic collar that allows both a flush-wall installation and a through-wall installation
- anti-rotation mechanisms for perfect functionality during tightening

Installation

For proper installation of the anchor, drill the hole perpendicular to the support with a drill bit of the appropriate diameter. The hole should be cleaned of drilling dust before applying the anchor; it is recommended not to use roto-percussion when drilling the hole on a wall with perforated brick so as not to break the internal bulkheads. Insert the anchor and carry out the desired installation.

Technical Features



Anchor

| ANCHOR MATERIAL | SCREW MATERIAL | MINIMUM DRILLING DEPTH | MAXIMUM FIXABLE THICKNESS | A | S | H | R |
|-----------------|---------------------------------------|------------------------|---------------------------|---------------|-------|---------|-------|
| POLYAMIDE 6 | 7-8 M ELECTROGALVANIZED TREATED STEEL | 65 MM | 15 MM | 8,4X16X1,6 MM | 50 MM | 7X70 MM | 10 MM |

| SKU | MODEL | PRICE |
|-------------|----------------------------|-------------------|
| 00000011885 | ANCHOR WITH HEX HEAD SCREW | €1.9 VAT EXCLUDED |

