ATEX VACUUM PUMP

Model DS PRO EX-2

Product informations

DS PRO EX-2, the ATEX vacuum pump designed to achieve high vacuum levels in systems operating with class A2L (R32) or A3 (R290) refrigerant gases; this device is to be used only in well-ventilated environments.

Product features

- equipped with a vacuum gauge but not solenoid valve
- equipped with a 5 m long tube with ballast valve necessary for evacuation of gases or vapors generated in the early stages of vacuum
- 5-meter long power cable to ensure operator safety

PUMP COMPONENTS	
1	DISCHARGE PIPE WITH BALLAST VALVE
2	VACUUM GAUGE
3	OIL TANK
4	OIL LEVEL SIGHT GLASS
5	OIL DRAIN PLUG
6	HANDLE
7	SUCTION FITTING

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

PUMP COMPONENTS	
8	ATEX SWITCH
9	ELECTRIC MOTOR
10	COOLING FAN COVER
11	BASE

Technical Features

ELECTRICAL SPECIFICATIONS	230V 50-60 HZ
POWER	3/4HP
FLOW RATE	170 L/MIN
ULTIMATE VACUUM	7,5 MICRONS
OIL CAPACITY	600 ML
WORKING TEMPERATURE	5°C ~ 40°C
CONNECTIONS	1/4" E 3/8" SAE
USABLE GAS	A2L-CLASS REFRIGERANTS, INCLUDING R290
WEIGHT	17,9 KG
DIMENSIONS	457X356X254 MM (WXHXD)

SKU	MODEL	PRICE
00000011190	ATEX VACCUM PUMP MOD. DS PRO EX-2 - 1 PCS.	**€1234.8 VAT EXCLUDED**

Via Marco Polo 33
35020 Albignasego
Padova – Italy


P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

ATEX Vacuum Pump












Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net