



ATEX VACUUM PUMP

Model DS PRO EX-2

Product informations

DS PRO EX-2, the ATEX vacuum pump designed to achieve high vacuum levels in systems operating with class A2L (R32) or A3 (R290) refrigerant gases; this device is to be used only in well-ventilated environments.

Product features

- equipped with a vacuum gauge but not solenoid valve
- equipped with a 5 m long tube with ballast valve necessary for evacuation of gases or vapors generated in the early stages of vacuum
- 5-meter long power cable to ensure operator safety

| <i>PUMP COMPONENTS</i> | |
|------------------------|-----------------------------------|
| 1 | DISCHARGE PIPE WITH BALLAST VALVE |
| 2 | VACUUM GAUGE |
| 3 | OIL TANK |
| 4 | OIL LEVEL SIGHT GLASS |
| 5 | OIL DRAIN PLUG |
| 6 | HANDLE |
| 7 | SUCTION FITTING |



ATEX Vacuum Pump

PUMP COMPONENTS

| | |
|----|-------------------|
| 8 | ATEX SWITCH |
| 9 | ELECTRIC MOTOR |
| 10 | COOLING FAN COVER |
| 11 | BASE |

Technical Features

| | |
|----------------------------------|---|
| ELECTRICAL SPECIFICATIONS | 230V 50-60 HZ |
| POWER | 3/4HP |
| FLOW RATE | 170 L/MIN |
| ULTIMATE VACUUM | 7,5 MICRONS |
| OIL CAPACITY | 600 ML |
| WORKING TEMPERATURE | 5°C ~ 40°C |
| CONNECTIONS | 1/4" E 3/8" SAE |
| USABLE GAS | A2L-CLASS REFRIGERANTS, INCLUDING R290 |
| WEIGHT | 17,9 KG |
| DIMENSIONS | 457X356X254 MM (WXHxD) |

| SKU | MODEL | PRICE |
|-------------|--|----------------------|
| 00000011190 | ATEX VACCUM PUMP MOD. DS PRO EX-2 - 1 PCS. | €1234.8 VAT EXCLUDED |



ATEX Vacuum Pump

