



Automatic Threaded Solenoid Valve for Gas EVP - EVPC NC Type

Catalogues and Products > Riscaldamento > Elettrovalvole per Gas > **Automatic Threaded Solenoid Valve for Gas EVP - EVPC NC Type**

AUTOMATIC THREADED SOLENOID VALVE FOR GAS EVP - EVPC NC TYPE

Normally closed with fast opening, max. pressure 200 mbar

Product informations

Automatic solenoid valves for gas **Mod. COMPACT**, normally closed with fast opening; opens the gas flow when the coil is electrically powered and closes it when the voltage is cut off.

Available on request also the version for BIOGAS (+ 10% on the cost).

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
ROOM TEMPERATURE	- 20°C ÷ + 60°C
SUPPLY VOLTAGES	230 V 50 - 60 HZ (ONLY SINGLE-PHASE, THE DEVICE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)
ELECTRICAL WIRING	STRAIN RELIEF M20X1.5
ABSORBED POWER	<ul style="list-style-type: none"> • 230 V = 18 VA (SKU 50383 / 50384) • 230 V = 30 VA / 9 VA (SKU 50360)
MAXIMUM WORKING PRESSURE	200 MBAR
N° CYCLES/HOUR	<ul style="list-style-type: none"> • 1800 CYCLES/HOUR ON=1S OFF=1S (SKU 50383 / 50384) • 1000 CYCLES/HOUR ON=1S OFF=1S (SKU 50360)
OPENING TIME	< 1 S



Automatic Threaded Solenoid Valve for Gas EVP - EVPC NC Type

CLOSING TIME	< 1 S
DEGREE OF PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)
CLASS	A
MATERIALS	ALUMINUM BODY
MECHANICAL STRENGTH	GROUP 2
FILTERING ORGAN	WIRE MESH WITH 1 MM
CONNECTIONS	1/2" FF - 3/4" FF - 1" FF (ACCORDING TO EN 10226)
COMPLIANCE	<ul style="list-style-type: none"> • REGULATION (EU) 2016/426 (APPLIANCES THAT BURN GASEOUS FUELS) • EMC DIRECTIVE 2014/30/EU • LVD DIRECTIVE 2014/35/EU • ROHS II DIRECTIVE 2011/65/EU

SKU	MODEL	PRICE
00000050360		€131.8 VAT EXCLUDED
00000050383		€107.0 VAT EXCLUDED
00000050384		€107.0 VAT EXCLUDED

