BLUE KIT BASIC 3.0

The complete boiler-saver kit

Product informations

- ***BLUE KIT BASIC 3.0*** consists of the magnetic filter *DSBLUE.PL* (*SKU 70049*), the polyphosphate dispenser *Dosablue ONE* (*SKU 70874*) and the *Neutral Acid Water 35K* neutralizing cartridge (*SKU 70894*).
- ***BLUE KIT BASIC 3.1*** consists of the *MINI DSBLUE.PL magnetic defanger (SKU 70044)*, *Dosablue ONE polyphosphate dispenser (SKU 70874)*, and *Neutral Acid Water 35K neutralizing cartridge (SKU 70894)*.
- ***BLUE KIT BASIC 3.2*** consists of the *MINI DSBLUE.PL magnetic defuser (SKU 70044)*, the *Dosablue ONE polyphosphate dispenser (SKU 70874)*, and the *Neutralizing Cartridge Compact Neutral Acid Water (SKU 70892)*.
- ***BLUE KIT BASIC 3.3*** consists of the *PLASTICMAG.PL (SKU 70038)*, the *Dosablue ONE polyphosphate dispenser (SKU 70874)*, and the *Neutralizing Cartridge Compact Neutral Acid Water (SKU 70892)*

Technical Features

SKU 70874	
90° CONNECTIONS	IN/OUT 1/2" MOBILE
MAX FLOW RATE	1,5 M^3/H
MAX PRESSURE	3,5 BAR
WORKING TEMPERATURE	0°C - 45°C
RECHARGE AUTONOMY	12 - 15 M^3
PRESSURE DROP	0,2 BAR
VASE MATERIAL	SAN

TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

SKU 70049	
CHEMICAL COMPATIBILITY	WATER / WATER AND GLYCOL
MAX INLET PRESSURE	3 BAR
WORKING TEMPERATURE	0 ÷ 90°C
DEGREE OF FILTRATION	800 □M
THREADED CONNECTIONS	G 3/4" FF UNI-EN-ISO 228
KV (RANGE WITH DP 1 BAR)	5,4 M^3/H
MAGNETIC FIELD INTENSITY	11000 GAUSS

SKU 70894	
VALID FOR BOILERS UP TO 35 KW	
LENGTH	220 MM
DIAMETER	47 MM
MAX PRESSURE	0,5 BAR
MAXIMUM TEMPERATURE	60°C
MAX CAPACITY	8 L/H
UNIT MATERIAL	PP
HOSE HOLDER MATERIAL	PP
MATERIAL FIXING SYSTEM	PP
NEUTRALIZING CHARGE IN CALCIUM CARBONATE ($CACO_3$)	
EPDM HYDRAULIC SEALS	

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

SKU 70894	
ACCESSORIES	• PAIR OF 3/4" STRAIGHT HOSE CONNECTORS • FIXING CLIP WITH Ø 50 MM SCREWS

SKU 70044	
CHEMICAL COMPATIBILITY	WATER / WATER AND GLYCOL
MAX INLET PRESSURE	3 BAR
WORKING TEMPERATURE	0 ÷ 90°C
DEGREE OF FILTRATION	800 □M
THREADED CONNECTIONS	G 3/4" M/F UNI-EN ISO 228
KV (RANGE WITH DP 1 BAR)	4,45 M^3/H
MAGNETIC FIELD INTENSITY	7000 GAUSS
DIMENSIONS	58X120X90 MM (AXBXC)
UNIT	CHROME-PLATED BRASS
CONNECTIONS	CHROME-PLATED BRASS FG 3/4" / 3/4" M
BALL VALVE	CHROME-PLATED BRASS
FILTERING ELEMENT	AISI 304 STAINLESS STEEL MESH
MAGNET	RUTHENIUM
SEALS	EPDM

SKU 70892	
MAXIMUM OPERATING PRESSURE	0,5 BAR

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

SKU 70892	
MAXIMUM OPERATING TEMPERATURE	45°C
FLOW RATE	3 L/H
MATERIALS	• BODY: PP • HOSE CONNECTOR: PP • FASTENING SYSTEM: PP • NEUTRALYZING CHARGE: CALCIUM CARBONATE ($CACO_3$) • HYDRAULIC SEALS: NBR
CONNECTIONS	3/4"
DIMENSIONS	LENGTH 238 MM

SKU 70038	
CHEMICAL COMPATIBILITY	WATER / WATER AND GLYCOL
MAX INLET PRESSURE	3 BAR
WORKING TEMPERATURE	0 ÷ 90°C
DEGREE OF FILTRATION	G 3/4" M/F UNI-EN ISO 228
KV (RANGE WITH DP 1 BAR)	5,4 M^3/H
MAGNETIC FIELD INTENSITY	9000 GAUSS
CONNECTIONS	3/4"
DIMENSIONS	92X62X110X195 MM (AXBXCXD)
MATERIAL	• BODY: POLIPROPILENE +30% FV • TAPS AND CONNECTIONS: BRASS CW 617N UNI EN 12165 NICKEL-PLATED • DIFFUSER ELEMENT: POLYPROPYLENE +30% PV • MAGNET: NEODYMIUM 9000 GAUSS

TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Blue Kit Basic 3.0

SKU	MODEL	PRICE
00000070074	BLUE-KIT BASIC 3.0	€129.8 VAT EXCLUDED
00000070061	BLUE-KIT BASIC 3.1	ON REQUEST
00000070062	BLUE-KIT BASIC 3.2	ON REQUEST
00000070063	BLUE-KIT BASIC 3.3	ON REQUEST









Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net