BOXED IMMERSION BITHERMOSTAT

Equipped With liquid expansion probe

Product informations

Double boxed immersion thermostat, with liquid expansion probes, unipolar, temperature regulator and temperature limiter, fail-safe for capillary breakage, complete with watertight protection sheath. Particularly suitable for appliances where temperature control and safety is required.

Technical Features

ELECTRICAL CONTACT CAPACITY	10 (2,5) A / 250 VAC
CONTACT	INTERRUPTED DUE TO TEMPERATURE INCREASE OR EXCHANGE
MAXIMUM HEAD TEMPERATURE	80°C
MAXIMUM BULB TEMPERATURE	125°C
TEMPERATURE RANGE	0°C ÷ 90°C - SAFETY 100°C
THERMAL GRADIENT	1°K/MIN

Via Marco Polo 33
35020 Albignasego
Padova – Italy


P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Boxed Immersion Bithermostat

DEGREE OF PROTECTION	IP40 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, BUT PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 1 MM)
SHEATH CONNECTION	G1/2"
SHEATH LENGTH	100 MM

SKU	MODEL	PRICE
00000R02909	REPLACEMENT COCKPIT FOR BITHERMOSTAT MOD. TLSC	€27.95 VAT EXCLUDED
00000R03097	BOXED IMMERSION BITHERMOSTAT WITH LIQUID EXPANSION PROBE - 0°C ÷ 90°C	€104.6 VAT EXCLUDED





TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net