BRASS THREADED SOLENOID VALVE FOR GAS

Normally closed with manual reset under voltage, max. pressure 500 mbar

Product informations

Normally closed solenoid valve for gas for gas with manual reset under voltage; it can be reset only in the presence of mains voltage and only when the gas detector does not give any danger signals.

NB. the valve will not open by simply powering the coil, you must manually press the reset mechanism.

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
ROOM TEMPERATURE	- 20°C ÷ + 60°C
SUPPLY VOLTAGES	230 V 50 - 60 HZ (ONLY SINGLE-PHASE, THE DEVICE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)
ELECTRICAL WIRING	ELECTRIC CABLE (LENGTH 3 M, WITH WIRE TERMINALS)
ABSORBED POWER	230 V = 9 VA
MAXIMUM WORKING PRESSURE	500 MBAR
CLOSING TIME	< 1 S
DEGREE OF PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)

TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

COIL PROTECTION	II 3G EX MC EC NC IIC T4 GC X - II 3D EX MC TC IIIC T135°C DC X - SUITABLE FOR EXPLOSIVE ATMOSPHERES
CLASSE	A
MATERIALS	BRASS BODY
MECHANICAL STRENGTH	GROUP 2
CONNECTIONS	1/2" FF - 3/4" FF - 1" FF
COMPLIANCE	• REGULATION (EU) 2016/426 (APPLIANCES THAT BURN GASEOUS FUELS) • EN 60079-0-7-14-15-18-31 - ATEX DIRECTIVE 2014/34/EU • EMC DIRECTIVE 2014/30/EU • LVD DIRECTIVE 2014/35/EU • ROHS II DIRECTIVE 2011/65/EU

SKU	MODEL	PRICE
00000060520	BRASS THREADED SOLENOID VALVE FOR GAS - 1/2" FF - 500 MBAR	€191.4 VAT EXCLUDED
00000060521	BRASS THREADED SOLENOID VALVE FOR GAS - 3/4" FF - 500 MBAR	€191.4 VAT EXCLUDED
00000060522	BRASS THREADED SOLENOID VALVE FOR GAS - 1" FF - 500 MBAR	€216.25 VAT EXCLUDED



TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net