



Catalogues and Products > Heating > Solenoid Valve for Gas > **Brass Threaded Solenoid Valve for Gas**

## BRASS THREADED SOLENOID VALVE FOR GAS

Normally closed with manual reset under voltage, max. pressure 500 mbar

### Product informations

Normally closed solenoid valve for gas for gas with manual reset under voltage; it can be reset only in the presence of mains voltage and only when the gas detector does not give any danger signals.

**NB.** the valve will not open by simply powering the coil, you must manually press the reset mechanism.

### Technical Features

<b>USE</b>	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
<b>ROOM TEMPERATURE</b>	- 20°C ÷ + 60°C
<b>SUPPLY VOLTAGES</b>	230 V 50 - 60 HZ (ONLY SINGLE-PHASE, THE DEVICE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)
<b>ELECTRICAL WIRING</b>	ELECTRIC CABLE (LENGTH 3 M, WITH WIRE TERMINALS)
<b>ABSORBED POWER</b>	230 V = 9 VA
<b>MAXIMUM WORKING PRESSURE</b>	500 MBAR
<b>CLOSING TIME</b>	< 1 S
<b>DEGREE OF PROTECTION</b>	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)



## Brass Threaded Solenoid Valve for Gas

<b>COIL PROTECTION</b>	II 3G EX MC EC NC IIC T4 GC X - II 3D EX MC TC IIIC T135°C DC X - SUITABLE FOR EXPLOSIVE ATMOSPHERES
<b>CLASSE</b>	A
<b>MATERIALS</b>	BRASS BODY
<b>MECHANICAL STRENGTH</b>	GROUP 2
<b>CONNECTIONS</b>	1/2" FF - 3/4" FF - 1" FF
<b>COMPLIANCE</b>	<ul style="list-style-type: none"> <li>• REGULATION (EU) 2016/426 (APPLIANCES THAT BURN GASEOUS FUELS)</li> <li>• EN 60079-0-7-14-15-18-31 - ATEX DIRECTIVE 2014/34/EU</li> <li>• EMC DIRECTIVE 2014/30/EU</li> <li>• LVD DIRECTIVE 2014/35/EU</li> <li>• ROHS II DIRECTIVE 2011/65/EU</li> </ul>

SKU	MODEL	PRICE
00000060520	BRASS THREADED SOLENOID VALVE FOR GAS - 1/2" FF - 500 MBAR	€191.4 VAT EXCLUDED
00000060521	BRASS THREADED SOLENOID VALVE FOR GAS - 3/4" FF - 500 MBAR	€191.4 VAT EXCLUDED
00000060522	BRASS THREADED SOLENOID VALVE FOR GAS - 1" FF - 500 MBAR	€216.25 VAT EXCLUDED

