

Centrifugal Pump with High Flow Rates



Catalogues and Products > Air-Conditioning > Condensate Discharge Accessories > **Centrifugal Pump with High Flow Rates**

CENTRIFUGAL PUMP WITH HIGH FLOW RATES

Flowtank model

Product informations

FLOWTANK, the centrifugal pump with high evacuation flow rates, designed for application in showcases, refrigerated counters and air conditioners with or without a collection tank, where the condensation water is particularly full of impurities.

Product features

- reversible tank that allows the installation of the pump in all configurations
- with input adapter to avoid all problems of connecting the boiler to the pump
- high performance

The kit includes

- FLOWTANK centrifugal pump
- 3 caps
- input adapter
- outlet adapter Ø 6/9 mm
- screws and plugs

Technical Features

POWER SUPPLY	230 V 50 HZ 80 W
--------------	------------------



Page: 1







MAXIMUM FLOW RATE	788 L/H	
MAX DISCHARGE	5,5 M	
TANK	1,3 L	
MAXIMUM TEMPERATURE OF THE LIQUID	60°C	
PH RESISTANCE	> 2,5	
DEGREE OF PROTECTION	IP20 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, BUT PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 12 MM)	
ALARM	INTEGRATO	
OUTLET DIAMETERS	 ORIGINAL OUTLET FOR PIPE 9/12 MM REDUCER FOR PIPE 6/9 MM 	
NON-RETURN VALVE REMOVABLE IN ¼ TURN		
PUMP DIMENSIONS	280X130X135 MM (BXDXH)	

SKU	MODEL	PRICE
00000011907	FLOWTANK PUMP	€187.9 VAT EXCLUDED









Centrifugal Pump with High Flow Rates













Page: 3