



Centrifugal Pump with High Flow Rates

Catalogues and Products > Air-Conditioning > Condensate Discharge Accessories > **Centrifugal Pump with High Flow Rates**

CENTRIFUGAL PUMP WITH HIGH FLOW RATES

Flowtank model

Product informations

FLOWTANK, the centrifugal pump with high evacuation flow rates, designed for application in showcases, refrigerated counters and air conditioners with or without a collection tank, where the condensation water is particularly full of impurities.

Product features

- reversible tank that allows the installation of the pump in all configurations and compact for easy accommodation in small spaces
- with input adapter to avoid all problems of connecting the boiler to the pump
- high performance
- universal, disconnectable electrical connection for easy installation and maintenance

The kit includes

- FLOWTANK centrifugal pump
- power/alarm cable
- outlet adapter Ø 6/9 mm
- screws and plugs

Technical Features

POWER SUPPLY	230 V 50 HZ 65 W
--------------	------------------


Centrifugal Pump with High Flow Rates

MAXIMUM FLOW RATE	800 L/H
MAX DISCHARGE	5,6 M
TANK	1,2 L
MAXIMUM TEMPERATURE OF THE LIQUID	60°C
PH RESISTANCE	> 2,5
DEGREE OF PROTECTION	IP24 (SPLASH-PROOF)
ALARM	INTEGRATED
OUTLET DIAMETERS	<ul style="list-style-type: none"> • ORIGINAL OUTLET FOR PIPE 9/12 MM • REDUCER FOR PIPE 6/9 MM
NON-RETURN VALVE REMOVABLE IN 1/4 TURN	
PUMP DIMENSIONS	280X130X129 MM (BXDXH)

SKU	MODEL	PRICE
00000011907	FLOWTANK PUMP	€187.9 VAT EXCLUDED





Centrifugal Pump with High Flow Rates

