



Catalogues and Products > Riscaldamento > Tecnogiunti > Coated Galvanized Rectilinear Transition Fitting

# COATED GALVANIZED RECTILINEAR TRANSITION FITTING

Dielectric threaded version

## **Product informations**

Transition fitting designed to allow the passage from a plant in plastic material (polyethylene) to a metal one, to allow fuel gas distribution plants to exit the ground. The joints of polyethylene pipes to metal pipes are made by means of a threaded connection for the conveyance of combustible gases under pressure.

This type of joint has the purpose of ensuring permanent electrical separation between the underground and the aerial part of a gas system, in order to protect the downstream part of the joint from any stray currents which could damage the pipe, favoring its corrosion.

## **Technical Features**

MATERIALS	<ul> <li>UNI EN 10255 STEEL TUBE COATED ACCORDING TO UNI 9099 - POLYCOAT</li> <li>PE100 SHANK S5 SDR 11 (PN16)</li> </ul>
THREADING	EXTERNAL THREAD (TAPER MALE) ACCORDING TO EN 10226-1 (R)



Viale L. Da Zara 10 35020 Albignasego Padova – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 1



### **Coated Galvanized Rectilinear Transition Fitting**



NORMATIVE REQUIREMENTS	<ul> <li>UNI EN 1555-3: PLASTIC PIPING SYSTEMS FOR THE DISTRIBUTION OF COMBUSTIBLE GASES - POLYETHYLENE (PE)</li> <li>UNI 9736: FITTINGS MANUFACTURED WITH MIXED METAL- POLYETHYLENE JOINT FOR USE IN COMBUSTION OF COMBUSTIBLE GASES, WATER AND OTHER FLUIDS UNDER PRESSURE AND METAL- POLYPROPYLENE FOR USE IN CONDUCTS FOR WATER AND OTHER FLUIDS UNDER PRESSURE</li> <li>ISO 17885: PLASTIC PIPING SYSTEMS - MECHANICAL FITTINGS FOR PRESSURE PIPING SYSTEMS</li> <li>UNI 9034: GAS DISTRIBUTION CONDUCTS WITH MAXIMUM WORKING PRESSURE LESS THAN OR EQUAL TO 0,5 MPA (5 BAR) - JOINTING MATERIALS AND SYSTEMS</li> </ul>
OPERATING TEMPERATURE	20°C

SKU	PE DIAMETER	DN			DACKACING
		"	MM	KG (SINGLE PIECE)	PACKAGING
20310	25 MM	3/4"	26,7	1,0	24 PCS.
20311	32 MM	1"	33,4	1,3	15 PCS.
20312	40 MM	1" 1/4	42,2	1,6	12 PCS.
20313	50 MM	1" 1/2	48,3	1,9	8 PCS.
20314	63 MM	2"	60,3	2,7	6 PCS.

SKU	MODEL	PRICE
0000020310	COATED DIELECTRIC THREADED TRANSITION FITTING - DN 3/4" - PE-D 25 MM	ON REQUEST



Viale L. Da Zara 10 35020 Albignasego Padova – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 2



### **Coated Galvanized Rectilinear Transition Fitting**



SKU	MODEL	PRICE
00000020311	COATED DIELECTRIC THREADED TRANSITION FITTING - DN 1" - PE- D 32 MM	ON REQUEST
0000020312	COATED DIELECTRIC THREADED TRANSITION FITTING - DN 1" 1/4 - PE-D 40 MM	ON REQUEST
00000020313	COATED DIELECTRIC THREADED TRANSITION FITTING - DN 1" 1/2 - PE-D 50 MM	ON REQUEST
0000020314	COATED DIELECTRIC THREADED TRANSITION FITTING - DN 2" - PE- D 63 MM	ON REQUEST





Viale L. Da Zara 10 35020 Albignasego Padova – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 3