



CONDENSING TRAP

For single wall rigid system

Product informations

Condensing trap, lower element of the flue system which plugs the lower part and which conveys the condensate formed inside into a 1/2" GAS threaded connection.

Product features

- made in diameters: Ø 60 mm - Ø 80 mm - Ø 100 mm - Ø 125 mm - Ø 160 mm - Ø 200 mm
- finished in RAL 9010 color (**Also available in black PPs*)

Technical Features

DESIGNATION	T120 H1 W 2 O00 LI E U
TYPE OF MATERIAL	SELF-EXTINGUISHING PPS
PRESSURE RESISTANCE	WITH EPDM GASKETS CONFORMING TO THE EN 14241 STANDARD
APPLICATION RANGE	CONDENSING BOILERS AND COOKING STEAM EXHAUST
CORROSION RESISTANCE	TYPE 2
SUITABLE FUELS	METHANE GAS
FIRE REACTION	CLASS "E" (ACCORDING TO EN 13501-1)
OPERATING TEMPERATURE	CONTINUOUS OPERATION UP TO 120°C WET UNDER PRESSURE WITH EPDM GASKET



Condensing Trap

SKU	D	D _{MAX}	A	H _{TOT}	THICKNESS
51285	Ø 60 MM	70	50	105	2,1
51288	Ø 80 MM	90	53	110	2,4
51740	Ø 100 MM	112	56	118	2,7
51360	Ø 125 MM	135	61	141	3
51361	Ø 160 MM	171	66	154	3
51362	Ø 200 MM	-	-	-	-

SKU	MODEL	PRICE
00000051285	CONDENSING TRAP - Ø 60 MM*	€4.3 VAT EXCLUDED
00000051288	CONDENSING TRAP - Ø 80 MM*	€4.65 VAT EXCLUDED
00000051360	CONDENSING TRAP - Ø 125 MM	ON REQUEST
00000051740	CONDENSING TRAP - Ø 100 MM*	€6.75 VAT EXCLUDED

