



## Daily and/or Weekly Digital Analog Chronothermostat

Catalogues and Products > Heating > Thermostats and Chronothermostats > **Daily and/or Weekly Digital Analog Chronothermostat**

# DAILY AND/OR WEEKLY DIGITAL ANALOG CHRONOTHERMOSTAT

Model CR308/G and CR309/S

## Product informations

Battery powered 3V analog digital chronothermostat, available with *daily programming (Mod. CR308/G)* and/or *weekly programming (Mod. CR309/S)*.

## Product features

- display Lcd 2" 2/3
- ON/OFF operation with adjustable differential from 0.3°C / 0.5°C / 0.7°C / 0.9°C or modulating with control period 7/10/15/20 min
- temperature set adjustment shown on the display
- 2 temperature levels + antifreeze fixed at 5°C
- minimum programming of 30 minutes
- permanent manual operation
- temperature lock
- telephone command input

### FUNCTIONS OF BUTTONS AND SYMBOLS

1	SETTING BUTTON: HOURS-MINUTES OR ROOM TEMPERATURE DISPLAY
2	SWITCH - TYPE OF OPERATING MODE
3	BATTERY COMPARTMENT
4	"TAPPET" KEY



## Daily and/or Weekly Digital Analog Chronothermostat

### FUNCTIONS OF BUTTONS AND SYMBOLS

5	ADJUSTMENT KNOB "COMFORT SET" TEMPERATURE
6	"SET REDUCTION" ADJUSTMENT KNOB (SAVING)
7	DAY SETTING BUTTON ( <i>ONLY WEEKLY MODEL</i> )
8	DISPLAY OF OPERATION IN PROGRESS
9	ACTIVATION VIA WEEKLY PROGRAMMER (WITH FLASHING INDICATOR)
10	VISUALIZATION OF THE INSERTED PROGRAM: <ul style="list-style-type: none"> <li>• INDEX ON = COMFORT</li> <li>• INDEX OFF = REDUCTION</li> </ul>
11	BATTERY INDICATOR: <ul style="list-style-type: none"> <li>• ALMOST FLAT (<i>BLINKING</i>)</li> <li>• FLAT (<i>CONSTANTLY LIT</i>)</li> </ul>
12	USER STATUS INDICATOR: <ul style="list-style-type: none"> <li>• BLINKING = RELAY ON</li> <li>• OFF = RELAY OFF</li> </ul>
13	FLASHING CURRENT 1/2H INDEX
14	CURRENT HOUR OR ROOM TEMPERATURE DETECTED / TEMPERATURE SETTING
15	"TAPPET" KEY
16	DAY ( <i>ONLY WEEKLY MODEL</i> )
17	RESET

## Technical Features



## Daily and/or Weekly Digital Analog Chronothermostat

<b>POWER SUPPLY</b>	TWO 1,5 V AA ALKALINE BATTERIES (DURACELL OR ENERGIZER RECOMMENDED)
<b>AUTONOMY</b>	2 YEARS
<b>TYPE OF DISCONNECTION AND DEVICE</b>	1/B/U ELECTRONIC
<b>SOFTWARE</b>	CLASS A
<b>RATED IMPULSE VOLTAGE</b>	4 KV
<b>TYPE OF OUTPUT</b>	RELAY WITH POTENTIAL FREE NO/COM/NC CHANGEOVER CONTACT - MAX 5(3) A/250 VAC
<b>INPUT FOR PHONE PROGRAMMER</b>	FOR POTENTIAL FREE NO CONTACT
<b>TYPE OF INSULATION</b>	CLASS II
<b>DEGREE OF PROTECTION</b>	IP30 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, BUT PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 2,5 MM)
<b>PROGRAMMABLE INDICES ON THE CLOCK</b>	48
<b>ANTIFREEZE TEMPERATURE</b>	+ 5°C
<b>THERMAL GRADIENT</b>	MAX 1K / 15 MIN
<b>CLOCK ACCURACY</b>	± 1 SEC/GG
<b>REGULATION RANGE</b>	5°C ÷ 37.7°C
<b>DIMENSIONS</b>	121,5 X 31,5 X 82 MM (WXDXH)
<b>COLOR</b>	WHITE



## Daily and/or Weekly Digital Analog Chronothermostat

SKU	MODEL	PRICE
00000080530	DAILY ANALOG DIGITAL CHRONOTHERMOSTAT - MOD. CR308/G	€118.75 VAT EXCLUDED
00000080532	WEEKLY DIGITAL ANALOG CHRONOTHERMOSTAT - MOD. CR309/S	€122.05 VAT EXCLUDED

