



Catalogues and Products > Heating > Riduttori di Pressione > **Filling Group**

FILLING GROUP

With interception tap and filter

Product informations

Filling group in brass, suitable for filling and stabilizing the pressure inside closed circuit heating systems, when the system pressure drops below the set level, this automatically opens, filling the water system until the correct pressure is restored.

Product complete with pressure gauge with rear connection (SKU R01597)

Product features

- it can be installed in any position, in fact the product is not affected by the effects of gravity during its operation
- the incoming water flow can be stopped manually, using the integrated stopcock
- for correct operation of the entire heating system, the recommended pressure must not exceed 2 bar
- integrated filter, stopcock and check valve
- external finish in yellow brass

Technical Features

MAX INLET PRESSURE	16 BAR
REGULATION RANGE	0,5 BAR - 4 BAR (PRE-SETTING 1.5 BAR)
MAX TEMPERATURE	80°C
CONNECTIONS	1/2" (FF ISO 228 THREAD)



Filling Group

MATERIAL	<ul style="list-style-type: none"> • BODY: YELLOW BRASS • MEMBRANE: BRASS • FILTER: STAINLESS STEEL
DIMENSIONS	140 X 122 MM (HXL)

SKU R01597	
CASE MATERIAL	ABS
GLASS MATERIAL	PLASTIC
QUADRANT MATERIAL	ABS
CLASS	1,6
MANUAL ELEMENT	COPPER ALLOY SPRING
WORKING TEMPERATURE	- 20°C ÷ + 80°C
COMPLIANT WITH THE STANDARD	UNI EN 837-1
CONNECTIONS	1/4" - POSTERIOR
DIAMETER	Ø 50 MM
PRESSURE	0 ÷ 6 BAR

SKU	MODEL	PRICE
00000070131	FILLING GROUP GRR - 1/2" - COMPLETE WITH PRESSURE GAUGE	€56.5 VAT EXCLUDED



Filling Group

