FIXED CALIBRATION SAFETY VALVE

Fixed setting 6 Bar

Product informations

Safety valve with fixed calibration used in solar systems for pressure control, when the pressure reaches the calibration pressure it opens by venting to atmosphere preventing the system pressure from reaching dangerous limits for the generator and components in the system.

Technical Features

SKU 70968	
MAX. PERCENTAGE OF GLYCOL	50%
NOMINAL PRESSURE	PN 10
MAX. WORKING TEMPERATURE	160°C
OPENING OVERPRESSURE	10%
CLOSURE DEVIATION	20%
CALIBRATION	6 BAR
MATERIALS	• BODY: BRASS CW167N • CONTROL ROD: BRASS CW617N • SCREW SEAL: FIBRE • MEMBRANE: EPDM • SPRING: STAINLESS STEEL • CONTROL KNOB: ABS

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net


Fixed Calibration Safety Valve

SKU 70968	
DIMENSIONS	• F 3/4" - ***A*** • F 3/4" - ***B*** • 24 MM - ***C*** • 66 MM - ***D*** • 25 MM - ***E***

SKU 70867	
CONNECTIONS	1/2" F
MAX. WORKING TEMPERATURE	160°C

SKU	MODEL	PRICE
00000070967	SAFETY VALVE - 1/2" F	€14.45 VAT EXCLUDED
00000070968	SAFETY VALVE - 3/4" F	€24.5 VAT EXCLUDED





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net