FLEXIBLE HOSES FOR PLACE GROUP

Version completely in stainless steel

Product informations

Flexible hoses for place group control entirely in stainless steel, with external coating in white PVC against saline oxidation.

Technical Features

OPERATING PRESSURE	20 BAR
WORKING FLUID	COMBUSTIBLE GASES
BURST PRESSURE	80 BAR
MAX TEMPERATURE	100°C
BENDING RADIUS (MINIMUM PERMISSIBLE IN STATIC CONDITIONS RP)	32 MM
RADIUS OF CURVATURE (MINIMUM FOR RC CYCLIC MOVEMENTS)	130 MM
LENGTH	60 CM - 120 CM
CONNECTION	FF SX CH 25

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Flexible Hoses for Place Group

SKU	MODEL	PRICE
00000006403	FLEXIBLE HOSE FOR PLACE GROUP - 120 CM - FF CONNECTION LEFT	€69.55 VAT EXCLUDED
00000006407	FLEXIBLE HOSE FOR PLACE GROUP - 60 CM - FF CONNECTION LEFT	€56.35 VAT EXCLUDED







Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net