



Catalogues and Products > Heating > Lpg Reduction Station > **LPG Reduction Group**

LPG REDUCTION GROUP

Version 1ST Stage - P2 0,5 bar

Product informations

LPG reduction group, version **1ST Stage**, composed by a complete line including regulator, condensate tank, needle tap, pressure gauge, safety valve and ball valve.

STRUCTURE OF THE REDUCTION GROUP	
A	DN INLET
B	REGULATOR
C	CONDENSATE TANK
D	NEEDLE TAP
E	PRESSURE GAUGE
F	SAFETY VALVE
G	BALL VALVE
H	DN OUTLET

Technical Features



LPG Reduction Group

SKU	FLOW RATE	INLET CONNECTION	OUTLET CONNECTION	TYPE OF REGULATOR	TYPE OF PRESSURE GAUGE	SAFETY VALVE	BALL VALVE	INLET PRESSURE	OUTLET PRESSURE	CONDENSATE TANK DIAMETER	NEEDLE TAP
13028	100 KG/H	DN 25	DN 25	ALFA 10 MODEL	Ø 60 - 2,5 BAR SETTING - 1/4" CONNECTION	1/4" - 2 BAR SETTING	M/F 1/4"	2 ÷ 18 BAR	0,5 BAR	Ø 4"	STEEL, 1/4"
13029	200 KG/H	DN 25	DN 50	ALFA 20 MODEL						Ø 4"	
13030	500 KG/H	DN 40	DN 65	ALFA 40 MODEL						Ø 5"	

SKU	MODEL	PRICE
00000013028	LPG REDUCTION GROUP 1ST STAGE - FLOW RATE 100 KG/H	€1177.05 VAT EXCLUDED
00000013029	LPG REDUCTION GROUP 1ST STAGE - FLOW RATE 200 KG/H	€1276.8 VAT EXCLUDED
00000013030	LPG REDUCTION GROUP 1ST STAGE - FLOW RATE 500 KG/H	€2812.95 VAT EXCLUDED

