



Catalogues and Products > Heating > Lpg Reduction Station > **Double Line Reduction Group for LPG**

DOUBLE LINE REDUCTION GROUP FOR LPG

Version 1ST stage with/without OPSO shut-off valve

Product informations

Double line reduction group for LPG version **1ST stage** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	HIGH PRESSURE REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	SAFETY VALVE
8	NEEDLE TAP
9	SQUARE BALL VALVE
10	MAX PRESSURE SHUT-OFF VALVE - <i>PRESENT ONLY IN SKU 13036</i>

Technical Features

FLOW RATE	200 KG/H
-----------	----------



Double Line Reduction Group for LPG

INLET CONNECTION	DN 25
OUTLET CONNECTION	DN 50
INLET PRESSURE	2 ÷ 18 BAR
OUTLET PRESSURE	0.5 BAR
TYPE OF REGULATOR	ALFA 31 MODEL
TYPE OF PRESSURE GAUGE	Ø 60 - 1/4" RADIAL CONNECTION
BUTTERFLY VALVE	DN 40 - PN 16
DISCHARGE BALL VALVE	1/4" CONNECTION - PN 16
SAFETY VALVE CONNECTION	1/4"
SQUARE BALL VALVE	1/2" - PN 16 CONNECTION
BALL VALVE	DN 25 - PN 40
CONDENSATE TANK DIAMETER	Ø 4"
MAX PRESSURE SHUT-OFF VALVE	OPSO - <i>PRESENT ONLY IN SKU 13036</i>
NEEDLE TAP	1/4" - PN 16

SKU	MODEL	PRICE
00000013035	DOUBLE LINE REDUCING GROUP FOR LPG 1ST STAGE - FLOW RATE 200 KG/H	€4189.5 VAT EXCLUDED
00000013036	DOUBLE LINE REDUCING GROUP FOR LPG 1ST STAGE - FLOW RATE 200 KG/H - WITH OPSO SHUT-OFF VALVE	€5446.35 VAT EXCLUDED



Double Line Reduction Group for LPG

