



Catalogues and Products > Heating > Lpg Reduction Station > **Double Line Reduction Group for LPG**

## DOUBLE LINE REDUCTION GROUP FOR LPG

Version 2ND Stage with/without OPSO shut-off valve, flow rate 200 kg/h

### Product informations

Double line reduction group for LPG version **2ND Stage** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	NEEDLE TAP
8	MAX PRESSURE SHUT-OFF VALVE - <i>PRESENT ONLY IN SKU 13049</i>

### Technical Features

<b>FLOW RATE</b>	200 KG/H
<b>INLET CONNECTION</b>	DN 40
<b>OUTLET CONNECTION</b>	DN 50



## Double Line Reduction Group for LPG

<b>INLET PRESSURE</b>	0,5 ÷ 2 BAR
<b>OUTPUT PRESSURE</b>	ON REQUEST
<b>TYPE OF REGULATOR</b>	ALFA 35 MODEL WITH RELIEF VALVE
<b>TYPE OF PRESSURE GAUGE</b>	Ø 60 - 1/4" RADIAL CONNECTION
<b>BUTTERFLY VALVE</b>	DN 50 - PN 16
<b>DISCHARGE BALL VALVE</b>	1/2" CONNECTION - PN 16
<b>CONDENSATE TANK DIAMETER</b>	Ø 4"
<b>MAX PRESSURE SHUT-OFF VALVE</b>	OPSO - <i>PRESENT ONLY IN SKU 13049</i>
<b>NEEDLE TAP</b>	1/4" - PN 40

SKU	MODEL	PRICE
00000013048	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H	€4650.35 VAT EXCLUDED
00000013049	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H - WITH OPSO SHUT-OFF VALVE	€5655.85 VAT EXCLUDED

