DOUBLE LINE REDUCTION GROUP FOR LPG

Version 2ND Stage with/without OPSO shut-off valve, flow rate 200 kg/h

Product informations

Double line reduction group for LPG version ***2ND Stage*** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	NEEDLE TAP
8	MAX PRESSURE SHUT-OFF VALVE - ***PRESENT ONLY IN SKU 13049***

Technical Features

FLOW RATE	200 KG/H
INLET CONNECTION	DN 40
OUTLET CONNECTION	DN 50


Via Marco Polo 33
35020 Albignasego
Padova – Italy


P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Double Line Reduction Group for LPG

INLET PRESSURE	0,5 ÷ 2 BAR
OUTPUT PRESSURE	ON REQUEST
TYPE OF REGULATOR	ALFA 35 MODEL WITH RELIEF VALVE
TYPE OF PRESSURE GAUGE	Ø 60 - 1/4" RADIAL CONNECTION
BUTTERFLY VALVE	DN 50 - PN 16
DISCHARGE BALL VALVE	1/2" CONNECTION - PN 16
CONDENSATE TANK DIAMETER	Ø 4"
MAX PRESSURE SHUT-OFF VALVE	OPSO - ***PRESENT ONLY IN SKU 13049***
NEEDLE TAP	1/4"- PN 40

SKU	MODEL	PRICE
00000013048	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H	**€4650.35 VAT EXCLUDED**
00000013049	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H - WITH OPSO SHUT-OFF VALVE	**€5655.85 VAT EXCLUDED**





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net