DOUBLE LINE REDUCTION GROUP FOR LPG

Version 2ND Stage with/without OPSO shut-off valve, flow rate 500 kg/h

Product informations

Double line reduction group for LPG version ***2ND Stage*** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BUTTERFLY VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	NEEDLE TAP
8	MAX PRESSURE SHUT-OFF VALVE - ***PRESENT ONLY IN SKU 13051***

Technical Features

FLOW RATE	500 KG/H
INLET CONNECTION	DN 50
OUTLET CONNECTION	DN 80


Via Marco Polo 33
35020 Albignasego
Padova – Italy


P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Double Line Reduction Group for LPG

INLET PRESSURE	0.5 ÷ 5 BAR
OUTPUT PRESSURE	35 MBAR
TYPE OF REGULATOR	ALFA 50 BP MODEL
TYPE OF PRESSURE GAUGE	Ø 60 - 1/4" RADIAL CONNECTION
BUTTERFLY VALVE	DN 50 - PN 16
DISCHARGE BALL VALVE	1/4" CONNECTION - PN 16
CONDENSATE TANK DIAMETER	Ø 6"
MAX PRESSURE SHUT-OFF VALVE	OPSO - ***PRESENT ONLY IN SKU 13050***
NEEDLE TAP	1/4"- PN 40

SKU	MODEL	PRICE
00000013050	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 500 KG/H	**€8001.95 VAT EXCLUDED**
00000013051	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 500 KG/H - WITH OPSO SHUT-OFF VALVE	**€9216.9 VAT EXCLUDED**





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net