



Anaerobic Sealant

Catalogues and Products > Riscaldamento > Sigillanti e Accessori per Sigillatura > **Anaerobic Sealant**

ANAEROBIC SEALANT

High resistance and/or permanent

Product informations

Anaerobic sealant for high strength metals (SKU 50954), to block and seal threaded joints, with high resistance to thermal shocks, vibrations, water, gases, oils and fuels, refrigeration fluids and various chemical agents.

Product features

- it can be used on all metals, both in free and forced couplings
- maintains sealing properties up to + 200°C

Permanent anaerobic sealant (SKU 50957) for metals with rapid polymerization and high mechanical resistance, to seal and block threaded joints and cylindrical couplings; with high resistance to thermal shocks, vibrations, chemical agents and aging.

NB. To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming. **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.


Anaerobic Sealant
Technical Features

SKU 50954	
MAX Ø FOR USE 2" - CLEARANCE 0,3 MM	
COLOR	GREEN
SURVEY	FLUORESCENT IN BLUE LIGHT
FLASH POINT	> + 100°C
MANIPOLATION	20 - 40 MINUTES
FUNCTIONAL HARDENING TIME	6 - 12 HOURS
FINAL HARDENING TIME	24 - 36 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 200°C
DVGW GAS APPROVED FOR THREADED JOINTS ACCORDING TO EN 751-1	
WRAS APPROVED FOR CONTACT WITH DRINKING WATER	

SKU 50957	
MAX Ø FOR USE 1 1/2" - CLEARANCE 0,2 MM	
COLOR	GREEN
SURVEY	FLUORESCENT IN BLUE LIGHT
FLASH POINT	> + 100°C
MANIPOLATION	<ul style="list-style-type: none"> • BRASS (BARE) < 1 MINUTE • CHROMED AND NICKEL-PLATED BRASS 3 - 6 MINUTES • STEEL 2 - 5 MINUTES • ALUMINUM 6 - 18 MINUTES



Anaerobic Sealant

SKU 50957

FUNCTIONAL HARDENING TIME	1 - 3 HOURS
FINAL HARDENING TIME	2 - 4 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 150°C
APPROVED FOR GAS (GAZ DE FRANCE)	

SKU	MODEL	PRICE
00000050954	HIGH RESISTANCE ANAEROBIC SEALANT 85-86 - 50 ML	€30.65 VAT EXCLUDED
00000050957	PERMANENT ANAEROBIC SEALANT 85-21 - 250 ML	€102.3 VAT EXCLUDED

