



Catalogues and Products > Riscaldamento > Elettrovalvole per Acqua > **Indirectly Operated Water Solenoid Valve**

## INDIRECTLY OPERATED WATER SOLENOID VALVE

Model 7321B PARKER NC

### Product informations

Indirectly operated normally closed solenoid valve for applications in the industrial and process markets, to be installed when precise and reliable water control is required; consisting of a brass body and a stainless steel operator rated for millions of life cycles. This product can optimize the total ownership costs in a broad range of heavy duty and high demanding applications in safe or harsh environment including ATEX.

*Supplied without coil.*

### Product features

- anti water hammer effect
- applications in firefighting, irrigation, water distribution, cooling and air conditioning

### Technical Features

SKU	CONNECTION	PASSAGE DIMENSIONS	MATERIALS	FLOW COEFFICIENT (L/MIN)	DIFFERENTIAL PRESSURE		GASKET	FLUID TEMPERATURE		FLOW RATE (M <sup>3</sup> /H)
					MIN AC / DC	MAX AC / DC		MIN	MAX	
503445	G 3/8"	Ø 13 MM	BODY: BRASS POSITION: BRASS	50 L/MIN	0.1 BAR	20 BAR	NBR	- 10°C	+ 90°C	3 M <sup>3</sup> /H



## Indirectly Operated Water Solenoid Valve

503446	G 1/2"	Ø 13 MM	BODY: BRASS POSITION: BRASS	50 L/MIN	0.1 BAR	20 BAR	NBR	- 10°C	+ 90°C	3 M <sup>3</sup> /H
503447	G 3/4"	Ø 20 MM	BODY: BRASS POSITION: BRASS	140 L/MIN	0.1 BAR	20 BAR	NBR	- 10°C	+ 90°C	8.4 M <sup>3</sup> /H
503448	G 1"	Ø 25 MM	BODY: BRASS POSITION: BRASS	160 L/MIN	0.1 BAR	20 BAR	NBR	- 10°C	+ 90°C	9.6 M <sup>3</sup> /H
503449	G 1" 1/4	Ø 35 MM	BODY: BRASS POSITION: BRASS	420 L/MIN	0.1 BAR	10 BAR	NBR	- 10°C	+ 90°C	25.2 M <sup>3</sup> /H
503450	G 1" 1/2	Ø 40 MM	BODY: BRASS POSITION: BRASS	500 L/MIN	0.1 BAR	10 BAR	NBR	- 10°C	+ 90°C	30 M <sup>3</sup> /H
503451	G 2"	Ø 50 MM	BODY: BRASS POSITION: BRASS	620 L/MIN	0.1 BAR	10 BAR	NBR	- 10°C	+ 90°C	37.2 M <sup>3</sup> /H
503452	G 2" 1/2	Ø 65 MM	BODY: BRASS POSITION: BRASS	1100 L/MIN	0.2 BAR	10 BAR	NBR	- 10°C	+ 90°C	66 M <sup>3</sup> /H
503453	G 3"	Ø 75 MM	BODY: BRASS POSITION: BRASS	1334 L/MIN	0.2 BAR	10 BAR	NBR	- 10°C	+ 90°C	80 M <sup>3</sup> /H

SKU	MODEL	PRICE
00000503445	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 3/8"	€92.75 VAT EXCLUDED
00000503446	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 1/2"	€76.9 VAT EXCLUDED



## Indirectly Operated Water Solenoid Valve

SKU	MODEL	PRICE
00000503447	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 3/4"	€114.2 VAT EXCLUDED
00000503448	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 1"	€139.9 VAT EXCLUDED
00000503449	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 1" 1/4	€377.15 VAT EXCLUDED
00000503450	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 1" 1/2	€414.85 VAT EXCLUDED
00000503451	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 2"	€513.65 VAT EXCLUDED
00000503452	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 2" 1/2	€1847.75 VAT EXCLUDED
00000503453	SOLENOID VALVE FOR WATER MOD. 7321B PARKER NC - 3"	€1847.75 VAT EXCLUDED

