PVC FLEXIBLE DUCT

Insulated 2-PLY model

Product informations

INSULATED PVC FLEXIBLE DUCT - 10 M

High-quality insulated flexible duct, designed for low- and medium-pressure air conditioning and ventilation systems requiring thermal insulation.
Easy to install on both round and oval fittings, it features a smooth inner surface to reduce pressure losses.
The inner core consists of a single layer of durable PVC encapsulating a high-tensile steel wire spiral helix; the outer layer is made of polyethylene (PE) and acts as a vapour barrier.

Use: Venting, Air Conditioning

Technical Features

COLOR	BLACK
OPERATING TEMPERATURE	-30°C ÷ 70°C
MAX OPERATING PRESSURE	UP TO 2500 PA
MAX AIR VELOCITY	25 M/S
LENGHT	10 M
FIRE REACTION	EN 13501 (NOT TESTED)*

***Version with B_Ls1d0 certification available on request**

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

PVC flexible duct

SKU	DIAMETRO	VELOCITÀ ARIA 8 MT/SEC		VELOCITÀ ARIA 10 MT/SEC	
		PORTATA ARIA M^3/H	PERDITA DI CARICO IN PA	PORTATA ARIA M^3/H	PERDITA DI CARICO IN PA
65001	Ø 82 MM	152	19	190	31
65002	Ø 102 MM	250	15	333	24
65003	Ø 127 MM	383	12	368	18
65004	Ø 152 MM	-	-	-	-
65005	Ø 160 MM	575	8	773	14
65007	Ø 203 MM	900	6,5	1151	10,5
65009	Ø 254 MM	1445	4,7	1843	7,5
65010	Ø 305 MM	-	-	-	-
65011	Ø 315 MM	2278	3,7	3105	6

SKU	MODEL	PRICE
00000065005	INSULATED DOUBLE LAYER PVC FLEXIBLE PIPE - Ø 160 MM	€20.65 VAT EXCLUDED



Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net