



Catalogues and Products > Air-Conditioning > Staffe > **Insulating Fixing**

## INSULATING FIXING

For walls with coat insulation

### Product informations

Professional fixing ideal fixing for blocking external units or suspended loads on buildings insulated with thermal insulation from 80 to 160 mm.

### Product features

- fiberglass-reinforced nylon insulation body, has its inside a barrier that interrupts thermal bridging by preventing condensation and drip points inside the masonry
- ideal for securing climate machines and suspended loads in general in buildings insulated with insulation
- suitable for different types of masonry, such as concrete, solid brick masonry or perforated masonry (when used with TCH, PE165 and THC PE300 injection resins)
- equipped with TOP ultra-performance meshed sleeve with anti-rotation and anti-unthreading fins, M12x200 threaded rod, plastic support washer, lock nut and M10x25 INOX fastening bolt
- *for the hanging fixing of air conditioning unit, it is always recommended to use 4 fixings: 2 on the crossbeam and 2 on the vertical metal struts*

### Technical Features

<b>THREADED ROD MATERIAL</b>	STEEL 4.8 EN ISO 898-1 ELECTROLYTIC GALVANIZING 7-8 µM
<b>MESHED COMPASS MATERIAL</b>	PE POLYETHYLENE
<b>WASHER MATERIAL</b>	PP POLYPROPYLENE



## Insulating Fixing

<b>BOLT MATERIAL</b>	STAINLESS STEEL AISI 304 - EN 10088
<b>CIRCUIT BREAKER MATERIAL</b>	PA6 GLASS FIBER FILLED POLYAMIDE
<b>TYPE OF COATS</b>	80-160 MM
<b>MINIMUM DRILLING DEPTH</b>	180 MM
<b>A</b>	40 MM
<b>B</b>	76 MM
<b>C</b>	M10
<b>D</b>	M12
<b>E</b>	M12
<b>F</b>	200 MM
<b>G</b>	40 MM
<b>H</b>	100 MM
<b>I</b>	M12
<b>R</b>	16 MM

SKU	MODEL	PRICE
00000011884	INSULATING FIXING FOR WALLS WITH COAT INSULATION	€67.65 VAT EXCLUDED



## Insulating Fixing

