



Catalogues and Products > Heating > Descaling Liquids and Washing Pumps > **LiquidBlue BIO Kit**

LIQUIDBLUE BIO KIT

For low temperature heating systems

Product informations

Ready to use kit for washing and protecting low temperature heating systems from the *TecnoBlue* line, composed of:

- *LiquidBlue 100*: corrosion inhibitor, scale inhibitor and biocide. (**SKU 70085**)
- *LiquidBlue 700*: product for the elimination of the bacterial load (algae and microorganisms). (**SKU 70086**)

Technical Features

LIQUIDBLUE 100	
CATEGORY	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
APPLICATION	BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS
APPEARANCE	LIQUID
COLOR	AMBER
PH	6,8
RELATIVE DENSITY	1,06
WORKING TEMPERATURE	FROM 10°C TO 130°C
SOLUBILITY WATER	SOLUBLE
WATER COMPATIBILITY	<ul style="list-style-type: none"> • MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS • MEDIUM HARD WATER • SOFTENED OR DEMINERALISED WATER


LiquidBlue BIO Kit

LIQUIDBLUE 100	
APPLICATION AND DOSAGE	LIQUIDBLUE 100 CAN BE INTRODUCED INTO THE SYSTEM BY THE DOSING PUMP, FEED TANK OR OTHER CONVENIENT POINT IN THE CIRCUIT. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE SYSTEM.</u>
SIZE	1 L

LIQUIDBLUE 700	
CATEGORY	CHEMICAL PRODUCT FOR COOLING WATER
APPLICATION	BIOCIDE, BROAD SPECTRUM ANTI-SLIME WITH BIODISPERSANT
APPEARANCE	LIQUID
COLOR	COLORLESS
PH	4,5 ± 1,5
RELATIVE DENSITY	1,15
SOLIDIFICATION POINT	< 0°C
SOLUBILITY IN WATER	COMPLETELY MISCIBLE
CONTAINERS TO AVOID	AVOID USING COMMON STEEL, COPPER AND ITS ALLOYS
APPLICATION AND DOSAGE	LIQUIDBLUE 700 CAN BE INTRODUCED INTO THE SYSTEM BY DOSING PUMPS WHICH INJECT THE PRODUCT PROPORTIONALLY TO THE REPLENISHMENT, OR WITH SHOCKS AT INTERVALS PROGRAMMED BY TIMER. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE SYSTEM.</u>
SIZE	1 L



LiquidBlue BIO Kit

SKU	MODEL	PRICE
00000070070	LIQUIDBLUE BIO KIT	€64.0 VAT EXCLUDED

