



## LiquidBlue TRIO Kit

Catalogues and Products > Heating > Descaling Liquids and Washing Pumps > **LiquidBlue TRIO Kit**

# LIQUIDBLUE TRIO KIT

For low temperature or mixed heating systems

## Product informations

Ready to use kit for washing and protecting low temperature or mixed heating systems from the *TecnoBlue* line, consisting of:

- *LiquidBlue* 100: corrosion inhibitor, scale inhibitor and biocide. (**SKU 70085**)
- *LiquidBlue* 400: pickling product, it brings the deposits back to the surface and restores the circulation of the radiant elements. (**SKU 70087**)
- *LiquidBlue* 700: product for the elimination of the bacterial load (algae and microorganisms). (**SKU 70086**)

## Technical Features

LIQUIDBLUE 100	
CATEGORY	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
APPLICATION	BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS
APPEARANCE	LIQUID
COLOR	AMBER
PH	6,8
RELATIVE DENSITY	1,06
WORKING TEMPERATURE	FROM 10°C TO 130°C
SOLUBILITY WATER	SOLUBLE


**LiquidBlue TRIO Kit**
**LIQUIDBLUE 100**

<b>WATER COMPATIBILITY</b>	<ul style="list-style-type: none"> <li>• MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS</li> <li>• MEDIUM HARD WATER</li> <li>• SOFTENED OR DEMINERALISED WATER</li> </ul>
<b>APPLICATION AND DOSAGE</b>	<b>LIQUIDBLUE 100</b> CAN BE INTRODUCED INTO THE SYSTEM BY THE DOSING PUMP, FEED TANK OR OTHER CONVENIENT POINT IN THE CIRCUIT. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE SYSTEM.</u>
<b>SIZE</b>	1 L

**LIQUIDBLUE 400**

<b>CATEGORY</b>	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
<b>APPLICATION</b>	ANTICORROSION DESCALING DISPERSANT IN CLOSED CIRCUITS
<b>APPEARANCE</b>	LIQUID
<b>COLOR</b>	BROWN YELLOW
<b>PH</b>	7,4 ± 0,5
<b>RELATIVE DENSITY</b>	1,1
<b>SOLIDIFICATION POINT</b>	< 0°C
<b>SOLUBILITY IN WATER</b>	COMPLETELY MISCELLANEOUS
<b>WORKING TEMPERATURE</b>	THE HIGH TEMPERATURE FAVORS THE PICKLING ACTION, A VALUE BETWEEN 80°C AND 130°C IS RECOMMENDED
<b>CONTAINERS TO AVOID</b>	AVOID USING COMMON STEEL, COPPER AND ITS ALLOYS
<b>APPLICATION AND DOSAGE</b>	<b>LIQUIDBLUE 400</b> MUST BE DOSED INTO THE CIRCUIT WITH A SUITABLE FILLING SYSTEM OR POURED DIRECTLY INTO THE EXPANSION TANK. THE OPTIMAL DOSAGE FOR CORRECT PROTECTION OF THE SYSTEM IS <u>1 LITER FOR EVERY 100 LITERS OF WATER CIRCULATING IN THE SYSTEM.</u>


**LiquidBlue TRIO Kit**
**LIQUIDBLUE 400**

SIZE	1 L
------	-----

**LIQUIDBLUE 700**

CATEGORY	CHEMICAL PRODUCT FOR COOLING WATER
APPLICATION	BIOCIDE, BROAD SPECTRUM ANTI-SLIME WITH BIODISPERSANT
APPEARANCE	LIQUID
COLOR	COLORLESS
PH	4,5 ± 1,5
RELATIVE DENSITY	1,15
SOLIDIFICATION POINT	< 0°C
SOLUBILITY IN WATER	COMPLETELY MISCELLANEOUS
CONTAINERS TO AVOID	AVOID USING COMMON STEEL, COPPER AND ITS ALLOYS
APPLICATION AND DOSAGE	LIQUIDBLUE 700 CAN BE INTRODUCED INTO THE SYSTEM BY DOSING PUMPS WHICH INJECT THE PRODUCT PROPORTIONALLY TO THE REPLENISHMENT, OR WITH SHOCKS AT INTERVALS PROGRAMMED BY TIMER. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE SYSTEM.</u>
SIZE	1 L

SKU	MODEL	PRICE
00000070071	LIQUIDBLUE TRIO KIT	€88.5 VAT EXCLUDED

## LiquidBlue TRIO Kit

