



Catalogues and Products > Heating > Descaling Liquids and Washing Pumps > **LiquidBlue 100**

LIQUIDBLUE 100

Corrosion inhibitor, antiscalant and biocide

Product informations

Solution for the complete protection of corrosive phenomena and limescale in boilers and heating systems, including those equipped with aluminum components.

Benefits

- prevents oxygen corrosion
- prevents oxide deposits
- specific for copper, steel and aluminum alloys
- inhibits the proliferation of bacteria and by-products
- easy to handle
- of simple analytical determination
- contains activity indicator
- contains no exhaust limiting substances

Application and Dosage

LiquidBlue 100 can be introduced into the system by the dosing pump, feed tank or other convenient point in the circuit. The optimal dosage for correct system protection is 1 liter for every 100 liters of water in the system.

Technical Features

CATEGORY	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
----------	--



LiquidBlue 100

APPLICATION	BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS
APPEARANCE	LIQUID
COLOR	AMBER
PH	6,8
RELATIVE DENSITY	1,06
WORKING TEMPERATURE	FROM 10°C TO 130°C
SOLUBILITY WATER	SOLUBLE
WATER COMPATIBILITY	<ul style="list-style-type: none"> • MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS • MEDIUM HARD WATER • SOFTENED OR DEMINERALISED WATER
SIZE	1 L

SKU	MODEL	PRICE
00000070085	LIQUIDBLUE 100 - 1 L	€25.55 VAT EXCLUDED

