



Catalogues and Products > Riscaldamento > Liquidi Disincrostanti e Pompe di Lavaggio > **LiquidBlue 400**

## LIQUIDBLUE 400

Pickling product, brings deposits to the surface and restores the circulation of radiant elements

### Product informations

Auxiliary chemical product for water treatment, pickling, antiscaling, anticorrosive and biocide for closed circuits; brings the deposits formed over time to the surface and restores the correct circulation of the radiant elements.

### Benefits

- exerts a descaling action on existing deposits
- it inhibits the formation of encrustations and promotes their dispersion
- it has a direct anticorrosive action on exposed metal surfaces
- complete formulation for closed circuits to be pickled completely
- chemically stable
- active in a wide pH range
- thermally stable
- liquid easy to manipulation and use
- works at neutral or alkaline pH: 6,5 - 10

### Application and Dosage

**LiquidBlue 400** must be dosed into the circuit with a suitable filling system or poured directly into the expansion tank. The optimal dosage for correct protection of the system is 1 liter for every 100 liters of water circulating in the system.



## Technical Features

<b>CATEGORY</b>	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
<b>APPLICATION</b>	ANTICORROSIVE DESCALING DISPERSANT IN CLOSED CIRCUITS
<b>APPEARANCE</b>	LIQUID
<b>COLOR</b>	BROWN YELLOW
<b>PH</b>	7,4 ± 0,5
<b>RELATIVE DENSITY</b>	1,1
<b>SOLIDIFICATION POINT</b>	< 0°C
<b>SOLUBILITY IN WATER</b>	COMPLETELY MISCIBLE
<b>WORKING TEMPERATURE</b>	THE HIGH TEMPERATURE FAVORS THE PICKLING ACTION, A VALUE BETWEEN 80°C AND 130°C IS RECOMMENDED
<b>CONTAINERS TO AVOID</b>	AVOID USING COMMON STEEL, COPPER AND ITS ALLOYS
<b>SIZE</b>	1 L

SKU	MODEL	PRICE
00000070087	LIQUIDBLUE 400 - 1 L	€26.7 VAT EXCLUDED

