LIQUIDBLUE HEAT PUMP

Biocidal, anticorrosive and antiscalant product, particularly suitable for heat pumps

Product informations

Auxiliary chemical product that inhibits bacterial growth, antiscaling and anticorrosive for closed circuits; ideal for circuits with temperatures between - 10°C and + 130°C. For professional use.

SPECIFIC FOR HEAT PUMPS

Benefits

- prevents oxygen corrosion
- it prevents and removes deposits thanks to the dispersing action of the product
- inhibits bacterial growth and by-products
- from easy manipulation
- of simple analytical determination
- contains activity indicator
- contains no exhaust limiting substances

Application and Dosage

LiquidBlue Heat Pump must be introduced into the circuit via a dosing pump, to be made proportional to the feed, the suggested injection point is the feed tank or another convenient point in the circuit. The optimal dosage for correct protection of the system is *1 liter for every 100 liters of water in the system.*

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Technical Features

CATEGORY	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
APPLICATION	ANTISCALANT ANTICORROSIVE BIOCIDE FOR CLOSED CIRCUITS
APPEARANCE	LIQUID
COLOUR	SLIGHTLY YELLOWISH
PH	7,8
RELATIVE DENSITY	1,04
SOLIDIFICATION POINT	< 0°C
SOLUBILITY WATER	COMPLETELY MISCIBLE
CONTAINERS TO AVOID	AVOID CONTACT WITH ALUMINIUM, ZINC, NICKEL, COPPER AND ITS ALLOYS
SIZE	• 1 L - ***SKU 70097*** • 5 L - ***SKU 70098***

SKU	MODEL	PRICE
00000070097	LIQUIDBLUE HEAT PUMP - 1 KG - 1 L	**€25.55 VAT EXCLUDED**
00000070098	LIQUIDBLUE HEAT PUMP - 5 KG - 5 L	**€119.1 VAT EXCLUDED**



TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net