



LOAD RELIEF VALVES

For approved tank

Product informations

The load limiting valves can be installed without restrictions in potentially explosive environments, such as tanks intended to contain category "C" liquid fuels (liquid having a flash point greater than 65°C)

Technical Features

<i>SKU R05518</i>	
<i>BODY</i>	ANODIZED ALUMINUM
<i>FLOATING</i>	BLACK HDPE (HIGH DENSITY POLYETHYLENE)
<i>ARM</i>	PA66 BLACK (POLYAMIDE)
<i>SLEEVE</i>	PA66 BLACK (POLYAMIDE)
<i>MECHANICAL CONNECTION</i>	STAINLESS STEEL EN 10270/3
<i>ATTACK</i>	Ø 2"

<i>SKU R05519</i>	
<i>BODY AND PLATE</i>	ALUMINUM
<i>LEVER</i>	TROPICALIZED STEEL



Load Relief Valves

SKU R05519	
FLOATING	PU (POLYURETHANE)
THREADING	UNI ISO 228/1
ATTACK	Ø 3"

SKU	MODEL	PRICE
00000R05518	CONNECTION Ø 2"	€120.9 VAT EXCLUDED
00000R05519	CONNECTION Ø 3"	€178.4 VAT EXCLUDED

