LOAD RELIEF VALVES

For approved tank

Product informations

The load limiting valves can be installed without restrictions in potentially explosive environments, such as tanks intended to contain category "C" liquid fuels (liquid having a flash point greater than 65°C)

Technical Features

SKU R05518	
BODY	ANODIZED ALUMINUM
FLOATING	BLACK HDPE (HIGH DENSITY POLYETHYLENE)
ARM	PA66 BLACK (POLYAMIDE)
SLEEVE	PA66 BLACK (POLYAMIDE)
MECHANICAL CONNECTION	STAINLESS STEEL EN 10270/3
ATTACK	Ø 2"

SKU R05519	
BODY AND PLATE	ALUMINUM
LEVER	TROPICALIZED STEEL

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Load Relief Valves

SKU R05519	
FLOATING	PU (POLYURETHANE)
THREADING	UNI ISO 228/1
ATTACK	Ø 3"

SKU	MODEL	PRICE
00000R05518	CONNECTION Ø 2"	€120.9 VAT EXCLUDED
00000R05519	CONNECTION Ø 3"	€178.4 VAT EXCLUDED







