



## LOAD RELIEF VALVES

For approved tank

### Product informations

The load limiting valves can be installed without restrictions in potentially explosive environments, such as tanks intended to contain category "C" liquid fuels (liquid having a flash point greater than 65°C)

### Technical Features

<i>SKU R05518</i>	
<i>BODY</i>	ANODIZED ALUMINUM
<i>FLOATING</i>	BLACK HDPE (HIGH DENSITY POLYETHYLENE)
<i>ARM</i>	PA66 BLACK (POLYAMIDE)
<i>SLEEVE</i>	PA66 BLACK (POLYAMIDE)
<i>MECHANICAL CONNECTION</i>	STAINLESS STEEL EN 10270/3
<i>ATTACK</i>	Ø 2"

<i>SKU R05519</i>	
<i>BODY AND PLATE</i>	ALUMINUM
<i>LEVER</i>	TROPICALIZED STEEL



**Load Relief Valves**

<b>SKU R05519</b>	
<b>FLOATING</b>	PU (POLYURETHANE)
<b>THREADING</b>	UNI ISO 228/1
<b>ATTACK</b>	Ø 3"

SKU	MODEL	PRICE
00000R05518	CONNECTION Ø 2"	€115.1 VAT EXCLUDED
00000R05519	CONNECTION Ø 3"	€169.9 VAT EXCLUDED

