



White Tube Coil

Catalogues and Products > Air-Conditioning > FastPipe® > **White Tube Coil**

WHITE TUBE COIL

Component of the FastPipe® SYSTEM

Product informations

The heart of **FastPipe® SYSTEM** is the pipe, available in different configurations with which it is possible to best design and customize a system.

The coiled tube is available in different configurations

- without coating (50 m coils)
- with 6 mm white coating
- with 6 mm UV-Pro coating (grey)

The hose also complies with the following regulations

- Global compliance with regulations: **UNI EN 1736:2009 (EN 1736:2008)**
- Coating (thermal conductivity): **UNI 8457 - UNI 9174**
- Coating (fire resistance): **UNI EN 1382:2014 - UL 94:2001**
- Resistance to permeation: **EN 1736 Top Performer Classe 1**

Technical Features

COMPATIBLE GASES	R410A - R32 - R134A - R404A - R407C - R454B (NOT COMPATIBLE WITH R22 GAS)
OPERATING TEMPERATURE	- 30°C ÷ + 110°C (ALSO WITHSTANDS NON-CONTINUOUS 130°C SPIKES)
MAXIMUM OPERATING PRESSURE	60 BAR



White Tube Coil

MINIMUM BENDING RADIUS

1/4"	3/8"	1/2"	5/8"
65 MM	95 MM	130 MM	170 MM

TIGHTENING TORQUE

1/4"	3/8"	1/2"	5/8"
15-17 NM (MAX. 20 NM)	28-32 NM (MAX. 35 NM)	38-42 NM (MAX. 45 NM)	60-68 NM (MAX. 80 NM)

SKU	MODEL	PRICE
00000011060	FASTPIPE® TUBE COIL WITH WHITE COATING Ø 1/4" - 50 M - 1 PCS.	€282.35 VAT EXCLUDED
00000011061	FASTPIPE® TUBE COIL WITH WHITE COATING Ø 3/8" - 50 M - 1 PCS.	€407.3 VAT EXCLUDED
00000011062	FASTPIPE® TUBE COIL WITH WHITE COATING Ø 1/2" - 50 M - 1 PCS.	€606.45 VAT EXCLUDED
00000011063	FASTPIPE® TUBE COIL WITH WHITE COATING Ø 5/8" - 50 M - 1 PCS.	€987.2 VAT EXCLUDED

