# MATASSA TUBO SENZA RIVESTIMENTO

Component of the FastPipe® SYSTEM

## Product informations

The heart of ***FastPipe® SYSTEM*** is the pipe, available in different configurations with which it is possible to best design and customize a system.

### The coiled tube is available in different configurations

- without coating (50 m coils)
- with 6 mm white coating
- with 6 mm UV-Pro coating (grey)

### *The hose also complies with the following regulations*

- Global compliance with regulations: **UNI EN 1736:2009 (EN 1736:2008)**
- Coating (thermal conductivity): **UNI 8457 - UNI 9174**
- Coating (fire resistance): **UNI EN 1382:2014 - UL 94:2001**
- Resistance to permeation: **EN 1736 Top Performer Classe 1**

## Technical Features

| | |
|---|---|
| *COMPATIBLE GASES* | R410A - R32 - R134A - R404A - R407C - R454B (***NOT COMPATIBLE WITH R22 GAS***) |
| *OPERATING TEMPERATURE* | - 30°C ÷ + 110°C (*ALSO WITHSTANDS NON-CONTINUOUS 130°C SPIKES*) |
| *MAXIMUM OPERATING PRESSURE* | 60 BAR |



TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

# Matassa Tubo senza Rivestimento

| *MINIMUM BENDING RADIUS* | | | |
|---|---|---|---|
| 1/4" | 3/8" | 1/2" | 5/8" |
| 65 MM | 95 MM | 130 MM | 170 MM |

| *TIGHTENING TORQUE* | | | |
|---|---|---|---|
| 1/4" | 3/8" | 1/2" | 5/8" |
| 15-17 NM (MAX. 20 NM) | 28-32 NM (MAX. 35 NM) | 38-42 NM (MAX. 45 NM) | 60-68 NM (MAX. 80 NM) |

| SKU | MODEL | PRICE |
|---|---|---|
| 00000012160 | FASTPIPE® TUBE COIL WITHOUT COATING Ø 1/4" - 50 M - 1 PCS. | €263.0 VAT EXCLUDED |
| 00000012161 | FASTPIPE® TUBE COIL WITHOUT COATING Ø 3/8" - 50 M - 1 PCS. | €305.05 VAT EXCLUDED |
| 00000012162 | FASTPIPE® TUBE COIL WITHOUT COATING Ø 1/2" - 50 M - 1 PCS. | €499.05 VAT EXCLUDED |
| 00000012163 | FASTPIPE® TUBE COIL WITHOUT COATING Ø 5/8" - 50 M - 1 PCS. | €769.8 VAT EXCLUDED |





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net