



MOTORIZED ZONE VALVE WITH TWO-WAY MICRO

For heating and/or air conditioning

Product informations

Zone valve designed for application in closed circuit cooling and heating water systems, equipped with manual open/close control with metal lever. The use of this valve is not recommended in systems that have substantial reclaimed water (open systems).

Synchron motor, spare for zone valves and actuators, fully insulated and waterproof with built-in reducer.

Technical Features

POWER SUPPLY	230 VAC (24 VAC)
WORKING TEMPERATURE OF FLUIDS	0°C ÷ 90°C
OPERATING AMBIENT TEMPERATURE	0°C ÷ 40°C
CLOSING / OPENING TIME	<ul style="list-style-type: none"> • ACTUATION TIME 10 TO 15 SECONDS • SPRING RETURN 4 AND 5 SECONDS
OPERATING PRESSURE	300 PSI / 2 BAR / 2.0 MPA



Motorized Zone Valve with Two-Way Micro

MATERIALS	<ul style="list-style-type: none"> • ACTIVATOR: SUPPORT BASE IN STAINLESS STEEL • LID: ALUMINUM • VALVE UNIT: FORGED BRASS • GASKET: NBR
------------------	--

SKU R02275 / R05576	
POWER SUPPLY	<ul style="list-style-type: none"> • 220 VAC 50 HZ (SKU R02275) • 24 VAC 50 HZ (SKU R02276)
ABSORBED POWER	6.5 W, 7 VA
GEARBOX EXIT DIRECTION	COUNTERCLOCKWISE ROTATION
WORKING TEMPERATURE	<ul style="list-style-type: none"> • FLUID: 0°C ÷ 90°C • ENVIRONMENT: 0°C ÷ 40°C

ORDER GUIDE					
SKU	CONNECTION	KV (CV) FACTOR	CLOSED - OFF P(MPA)	WEIGHT	DIMENSIONS
R05293	1/2" FF	2.2 (2.5)	0.18	700 G	70 X 23 X 86 MM (AXBXC)
R05294	3/4" FF	3.0 (3.5)	0.16	850 G	87 X 23 X 93 MM (AXBXC)



Motorized Zone Valve with Two-Way Micro

ORDER GUIDE

R05295	1" FF	6.9 (8.0)	0.14	1000 G	94 X 25 X 95 MM (AXBXC)
--------	-------	-----------	------	--------	-------------------------------

SKU	MODEL	PRICE
00000R02275	SYNCRON MOTOR - 220 V 50 HZ	€25.8 VAT EXCLUDED
00000R02276	SYNCRON MOTOR - 24 V 50 HZ	€25.8 VAT EXCLUDED
00000R05293	MOTORIZED ZONE VALVE - 1/2" FF	€58.05 VAT EXCLUDED
00000R05294	MOTORIZED ZONE VALVE - 3/4" FF	€72.5 VAT EXCLUDED
00000R05295	MOTORIZED ZONE VALVE - 1" FF	€85.25 VAT EXCLUDED

