



Catalogues and Products > Air-Conditioning > Fittings in Copper and Brass > **Nylog Sealant**

NYLOG SEALANT

Elastic sealant for flares

Product informations

Nylog, viscoelastic fluid derived from oil (POE or PAG) for refrigerant compressors; thanks to its chemical composition, *Nylog* does not harden and does not contaminate the refrigeration circuits, as it is derived from the same lubricants used in the refrigeration field. Threaded connections coated with *Nylog* will block leaks due to high internal pressure, while, if used to coat gaskets, they will never dry out and will always remain protected from its lubricating action.

Product features

- it does not harden
- it does not contaminate the refrigeration circuits
- resists vibrations
- not corrosive

Technical Features

- Working temperature: $-35^{\circ}\text{C} \div +175^{\circ}\text{C}$
- Compatible with synthetic oils such as POE and PAG and has a high degree of solubility with mineral oils and AlkylBenzene AB
- ***Do not use Nylog in environments with high oxygen concentration and strong oxidants***
- Viscosity: $100 \div 110$ cPs
- *Nylog Blue is derived from synthetic oil and therefore compatible with Gas R410a, R407c and R134a*
- Tested on HVAC systems, and is completely miscible and compatible with systems that use synthetic oils (eg POE)



Nylog Sealant

SKU	MODEL	PRICE
00000050926	NYLOG SEALANT - 30 ML	€29.3 VAT EXCLUDED

