



## PASTE SEALANT

Approved for gas and LPG high pressure (A.G.A.) and oxygen (BAM)

### Product informations

Paste sealant for threaded joints, suitable for gas, LPG, compressed air, oil and fuels, industrial fluids, CFCs, drinking water and various chemical substances; its low coefficient of friction ensures easy assembly and prevents the sealant from dripping during hardening.

### Product features

- replaces PTFE and hemp tapes
- the hardened product forms a tough film with medium disassembly resistance
- ease of screwing and tenacious fixing

**NB.** To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming). **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

### Technical Features

MAX Ø FOR USE 2" - CLEARANCE 0,3 MM	
COLOR	YELLOW
DETECTION	FLUORESCENT IN BLUE LIGHT



## Paste Sealant

<b>POINT OF INFIMMABILITY</b>	> + 100°C
<b>HANDLING TIME</b>	15 - 30 MINUTES
<b>HARDENING TIME</b>	1 - 2 HOURS
<b>TEMPERATURE RANGE</b>	- 55°C ÷ + 150°C
<b>APPROVED FOR LPG UP TO 20 BAR AND 2" DIAMETER (AGA)</b>	
<b>APPROVED FOR GASEOUS OXYGEN UP TO 10 BAR AND + 60°C (BAM)</b>	

SKU	MODEL	PRICE
00000050304	PASTE SEALANT 58-11 - 50 ML	€16.2 VAT EXCLUDED
00000050305	PASTE SEALANT 58-11 - 250 ML	€50.4 VAT EXCLUDED

