



Paste Sealant

Catalogues and Products > Riscaldamento > Sigillanti e Accessori per Sigillatura > **Paste Sealant**

PASTE SEALANT

Approved for gas and LPG high pressure (A.G.A.) and oxygen (BAM)

Product informations

Paste sealant for threaded joints, suitable for gas, LPG, compressed air, oil and fuels, industrial fluids, CFCs, drinking water and various chemical substances; its low coefficient of friction ensures easy assembly and prevents the sealant from dripping during hardening.

Product features

- replaces PTFE and hemp tapes
- the hardened product forms a tough film with medium disassembly resistance
- ease of screwing and tenacious fixing

NB. To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming. **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

Technical Features

MAX Ø FOR USE 2" - CLEARANCE 0,3 MM	
COLOR	YELLOW
DETECTION	FLUORESCENT IN BLUE LIGHT



Paste Sealant

POINT OF INFIMMABILITY	> + 100°C
HANDLING TIME	15 - 30 MINUTES
HARDENING TIME	1 - 2 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 150°C
APPROVED FOR LPG UP TO 20 BAR AND 2" DIAMETER (AGA)	
APPROVED FOR GASEOUS OXYGEN UP TO 10 BAR AND + 60°C (BAM)	

SKU	MODEL	PRICE
00000050304	PASTE SEALANT 58-11 - 50 ML	€16.2 VAT EXCLUDED
00000050305	PASTE SEALANT 58-11 - 250 ML	€47.5 VAT EXCLUDED

