



## PURE ACETIC SILICONE

High elasticity pure acetic silicone

### Product informations

Acetic silicone even with characteristics of high elasticity, adhesion and resistance to high and low temperatures; suitable for non-porous materials, such as glass, ceramic, aluminum, many plastics (excluding PE, PP, PTFE), not suitable for mirrors, fibrous and porous materials, natural stones.

### Product features

- not paintable
- suitable for applications in environments subject to humidity and hot-humid environments such as bathrooms, sanitary ware, swimming pools, etc.
- excellent elasticity
- resistance to aging, UV rays and chemicals
- *TOTAL RESISTANCE TO MOLD, does not blacken and does not stain even in constantly humid environments*

### Technical Features

<b>DENSITY</b>	0,97 G/CM <sup>3</sup>
<b>WORKABILITY TIME</b>	12 MINUTES
<b>TIME FOR "PEEL MAKING"</b>	25 MINUTES
<b>"HARDENING" TIME (3 MM LAYER)</b>	24 HOURS
<b>HARDNESS</b>	18



## Pure Acetic Silicone

<b>CONTENT</b>	280 ML
<b>CONSERVATION</b>	16 MONTHS IN A DRY PLACE WITH A TEMPERATURE BETWEEN 5°C AND 25°C
<b>RESISTANCE TO TEMPERATURE</b>	- 40°C ÷ + 100°C

SKU	MODEL	PRICE
00000050930	TRANSPARENT ACETIC SILICONE - 280 ML	€11.7 VAT EXCLUDED
00000050931	WHITE ACETIC SILICONE - 280 ML	€12.1 VAT EXCLUDED

