



Catalogues and Products > Heating > Gas Meters, Brackets and Accessories for Meters > **Quantimeters / Flow**Meters with Mechanical or Electronic Numerator

QUANTIMETERS / FLOW METERS WITH MECHANICAL OR ELECTRONIC NUMERATOR

Model QA

Product informations

QA, flow meters with mechanical (QA) very safe for the wide range of flow rates and for the different needs of companies, the operation is based on the principle of the turbine, the rotation of the impeller is proportional to the volume of the gas flow and is recorded using a mechanical or electronic numerator. The self-lubricating bearings guarantee perfect maintenance-free operation of the Quantometer, while the Quantimeter itself can be installed very easily, as it can be mounted in any position (horizontal, vertical, etc.). The direction of flow is indicated on the meter body with an arrow.

Product features

- in production and heating processes, the quantometers allow precise control and optimization of energy
- compact gas meter
- does not require maintenance
- instant flow rate
- high resolution volume (decimal)
- measurement ratio up to 1:20
- overload up to 160% of the maximum capacity
- within a wide measuring range the accuracy is independent of the physical characteristics of the gas such as density, pressure and temperature



Page: 1





Applications

- gas type: methane, city gas, natural gas, not corrosive gases, inert gases and oxygen
- fields of application: chemical, food, petrochemical, district heating and power generation industries
- tasks: measurement, control, regulation and recording

Technical Features

SIZE	QA 10 - QA 1000	
FLOW RATES	1,6 - 1600 M ³ /H	
NOMINAL DIAMETERS	DN25 - DN150	
BODY MATERIAL	ALUMINUM	
MODEL QA	7 POSITION MECHANICAL NUMERATOR	
GAS TEMPERATURE	- 10°C ÷ + 60°C	
INSTANT CAPACITY	 HIGH RESOLUTION VOLUME (DECIMAL) MEASUREMENT RATIO UP TO 1:20 OVERLOAD UP TO 160% OF THE MAXIMUM CAPACITY WITHIN A WIDE MEASURING RANGE THE PRESSURE IS INDEPENDENT OF THE PHYSICAL CHARACTERISTICS OF THE GAS SUCH AS DENSITY, PRESSURE AND TEMPERATURE 	
PROTECTION CLASS	• QA MODEL: IP52 (PROTECTED AGAINST DRIPPING WATER AT AN ANGLE WITHIN ± 15° AND PROTECTED AGAINST DUST, SUCH THAT IT DOES NOT INTERFERE WITH THE OPERATION OF THE DEVICE)	







INTERFACE / OUTPUTS

- QA REED CONTACT E1
- QA EXIT NAMUR E 200 (ACCORDING TO EN50227)
- M-BUS INTERFACE (EN 14349)

MODEL	QA/10 - QA/40 - GI	QA/10 - QA/40 - GI	QA/65 - QA/1000 - Z I
COMBUSTIBLE GASES	4 BAR	4 BAR	20 BAR
MEDIUM / MAXIMUM PRESSURE	16 BAR	16 BAR	-
FLOW RATE M ³ /H	• QA/10 DN25: 1.6 - 16 • QA/16 DN25: 2 - 25 • QA/25 DN25: 2.5 - 40 • QA/40 DN 25: 3.3 - 65	-	-
NOMINAL DIAMETER	25	40	50 - 80 - 100 - 150
OUTPUTS / VALUES PULSES	10 IMP/ 500 IMP/M ³	250 IMP/M ³	 QA 65: 250 IMP/M³ QA 100 - 650: 187.5 IMP/M³







sku	MODEL	PRICE
00000050660	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/10 DN25 MODEL	€2560.0 VAT EXCLUDED
00000050661	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/16 DN25 MODEL	€2560.0 VAT EXCLUDED
00000050662	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/25 DN25 MODEL	€2560.0 VAT EXCLUDED
00000050663	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/40 DN25 MODEL	€2560.0 VAT EXCLUDED
00000050664	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/65 DN50 MODEL	€3560.0 VAT EXCLUDED
00000050665	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/100 DN80 MODEL	€4400.0 VAT EXCLUDED
00000050666	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/160 DN80 MODEL	€4400.0 VAT EXCLUDED
00000050667	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/250 DN80 MODEL	€4400.0 VAT EXCLUDED
00000050668	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/250 DN100 MODEL	€5080.0 VAT EXCLUDED
00000050669	QUANTOMETER WITH MECHANICAL NUMERATOR - QA/400 DN100 MODEL	€5080.0 VAT EXCLUDED



