QUICK SEALANT

For hydraulic and pneumatic connection

Product informations

Anaerobic sealant for metals with medium mechanical strength, seals hydraulic and pneumatic connection, gas, water, GPL, hydrocarbons, oils and various chemical agents.

Product features

- intermediate fixing
- highly resistant to temperature, corrosion, shocks and vibrations

NB. To seal PVC, PP or Nylon fittings, ***use only P.T.F.E. based sealant*** (*SKU 50950 / 50951*) by ***pre-treating*** the plastic threads with ***the activator*** (*SKU 50959*), ***screw and tighten within 1 minute*** (longer waiting times can break the sealant film that is already forming. ***Do not use the thread sealer*** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

Technical Features

MAX Ø FOR USE 3/4" - CLEARANCE 0,15 MM	
COLOR	BROWN
SURVEY	FLUORESCENT IN BLUE LIGHT
FLASH POINT	> + 100°C

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Quick Sealant

MANIPOLATION	10 - 20 MINUTES
FUNCTIONAL HARDENING TIME	1 - 3 HOURS
FINAL HARDENING TIME	3 - 6 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 150°C

SKU	MODEL	PRICE
00000050956	FAST SEALANT 53-14 - 250 ML	€83.2 VAT EXCLUDED



Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net