



## QUICK SEALANT

For hydraulic and pneumatic connection

### Product informations

Anaerobic sealant for metals with medium mechanical strength, seals hydraulic and pneumatic connection, gas, water, GPL, hydrocarbons, oils and various chemical agents.

### Product features

- intermediate fixing
- highly resistant to temperature, corrosion, shocks and vibrations

**NB.** To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming. **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

### Technical Features

<b>MAX Ø FOR USE 3/4" - CLEARANCE 0,15 MM</b>	
<b>COLOR</b>	BROWN
<b>SURVEY</b>	FLUORESCENT IN BLUE LIGHT
<b>FLASH POINT</b>	> + 100°C



## Quick Sealant

<b>MANIPULATION</b>	10 - 20 MINUTES
<b>FUNCTIONAL HARDENING TIME</b>	1 - 3 HOURS
<b>FINAL HARDENING TIME</b>	3 - 6 HOURS
<b>TEMPERATURE RANGE</b>	- 55°C ÷ + 150°C

SKU	MODEL	PRICE
00000050956	FAST SEALANT 53-14 - 250 ML	€83.2 VAT EXCLUDED

