



Catalogues and Products > Heating > Methane/lpg Regulators for Civil - Industrial Applications > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Alfa 80 BP series, with balanced direct action regulation

Product informations

Alfa 80 BP series regulator with balanced direct action, equipped with external sensing line, suitable for the use of not corrosive gases as methane and LPG.

Also available the version with minimum and maximum pressure shut-off valve downstream (sku 2630).

Technical Features

FLOW RATE	SEE TABLE UNDERLYING
INLET CONNECTION	DN 80
OUTPUT CONNECTION	DN 80
INLET PRESSURE	0,5 ÷ 5 BAR
OUTPUT PRESSURE	0,2 ÷ 1 BAR
STANDARD OUTPUT PRESSURE	ON REQUEST
WORKING TEMPERATURE	- 20°C ÷ + 60°C
EXTERNAL SENSING LINE	Ø 14



Low Pressure Regulator

MATERIALS	<ul style="list-style-type: none"> • BODY: GS 400 CAST IRON • HEADER: STEEL • SEAL: NITRILE RUBBER NBR OR HNBR • MEMBRANE: SANDWICH RUBBERIZED FABRIC
DIMENSIONS	560 X 298 X 140 MM

FLOW RATE TABLE M³/H	INLET PRESSURE			
	0,3 BAR	0,5 BAR	1 BAR	1,5 BAR
25 MBAR	1111 M ³ /H	1470 M ³ /H	2719 M ³ /H	2782 M ³ /H
50 MBAR	1071 M ³ /H	1445 M ³ /H	2169 M ³ /H	2794 M ³ /H
100 MBAR	981 M ³ /H	1391 M ³ /H	2146 M ³ /H	2783 M ³ /H
150 MBAR	869 M ³ /H	1328 M ³ /H	2119 M ³ /H	2769 M ³ /H
200 MBAR	726 M ³ /H	1255 M ³ /H	2089 M ³ /H	2754 M ³ /H
300 MBAR	-	1066 M ³ /H	2017 M ³ /H	2717 M ³ /H

OUTLET PRESSURE

To obtain the LPG flow rates in kg/h, multiply the values in red by 1,42.

SKU	MODEL	PRICE
00000002628	ALFA 80 BP SERIES REGULATOR - DN 80 - DN 80 CONNECTION	€6179.55 VAT EXCLUDED
00000002630	ALFA 80 BP SERIES REGULATOR - DN 80 - DN 80 CONNECTION - WITH BLOCK	€7583.0 VAT EXCLUDED



Low Pressure Regulator

