HIGH PRESSURE REGULATOR

Model APZ 12 with pressure gauge, flow rate 12 kg/h

Product informations

High-pressure regulator ***Mod. APZ 12*** complete with pressure gauge, designed to make the gas pressure coming out of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	GPL
FLOW RATE	12 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 16 BAR
OUTLET PRESSURE	0 ÷ 4 BAR - EXTERNAL SETTING
GAUGE PRESSURE RANGE	0 ÷ 6 BAR
CONNECTIONS	IN LEFT NUT CH 25 H16 - OUT 1/4" F

SKU	MODEL	PRICE
00000000927	LOW PRESSURE REGULATOR MOD. APZ 12 WITH PRESSURE GAUGE - IN LEFT NUT CH 25 H16 - OUT 1/4" F - FLOW RATE 12 KG/H	**€42.65 VAT EXCLUDED**

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

High Pressure Regulator







Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net