



Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **High Pressure Regulator**

HIGH PRESSURE REGULATOR

Model APZ 25, flow rate 25 kg/h

Product informations

High pressure regulator **Mod. APZ 25** complete with pressure gauge and safety valve, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	25 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	<ul style="list-style-type: none"> • 1 ÷ 16 BAR (SKU 930) • 2 ÷ 16 BAR (SKU 932)
SAFETY VALVE SETTING	2,5 ÷ 3 BAR
GAUGE PRESSURE RANGE	0 ÷ 6 BAR
OUTLET PRESSURE	<ul style="list-style-type: none"> • 0,5 BAR - FIXED SETTING (SKU 930) • 1,5 BAR - FIXED SETTING (SKU 932)
CONNECTION	IN LEFT NUT CH 25 H16 - OUT 3/8" F



High Pressure Regulator

MATERIALS	<ul style="list-style-type: none"> • BODY: BRASS FOR PRESSING AND EUROPEAN STANDARD EN CV 617 • COVER: ZAMAK PAINTED WITH EPOXY POWDERS AND BURNT AT 180°C • MEMBRANE: APPROVED NBR RUBBER REINFORCED WITH POLYESTER CANVAS
------------------	--

SKU	MODEL	PRICE
00000000930	HIGH PRESSURE REGULATOR APZ 25 MODEL - IN LEFT NUT CH 25 H16 - OUT 3/8" F - FLOW RATE 25 KG/H - FIXED SETTING 0,5 BAR	€75.3 VAT EXCLUDED
00000000932	HIGH PRESSURE REGULATOR APZ 25 MODEL - IN LEFT NUT CH 25 H16 - OUT 3/8" F - FLOW RATE 25 KG/H - FIXED SETTING 1,5 BAR	€78.85 VAT EXCLUDED





High Pressure Regulator

