LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 7 kg/h

Product informations

Low pressure regulator with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	7 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 4 BAR
OUTLET PRESSURE	22 ÷ 50 MBAR
CONNECTION	IN 1/4" F - OUT 3/8" F
MATERIALS	• BODY AND LID: ZINC ALLOY • DIAPHRAGM AND GASKET: ELASTOMER

SKU	MODEL	PRICE
00000000800	LOW PRESSURE REGULATOR - IN 1/4" F OUT 3/8" F - FLOW RATE 7 KG/H	€47.5 VAT EXCLUDED

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Low Pressure Regulator





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net