



Catalogues and Products > Heating > Lpg regulators for domestic use, high and low pressure > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Economical model with safety relief valve incorporated, flow rate 10 kg/h

Product informations

Economical type low pressure regulator with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	10 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 11 BAR
OUTLET PRESSURE	ADJUSTABLE 20 ÷ 50 MBAR
PRODUCTION CALIBRATION	30 MBAR
CONNECTIONS	<ul style="list-style-type: none"> • IN 1/2" F - OUT 1/2" F (SKU 822) • IN LEFT NUT CH 25 - OUT 1/2" F (SKU 823)
MATERIALS	<ul style="list-style-type: none"> • BODY AND COVER: ZINC ALLOY (ZAMA) • BODY PROTECTED BY GALVANIC TREATMENT (YELLOW ZINC PLATING) • COVER PROTECTED BY EPOXY POWDER COATING • COMPONENTS: NBR RUBBER, COMPLIANT WITH STANDARD EN 549



Low Pressure Regulator

SKU	MODEL	PRICE
00000000822	LOW PRESSURE REGULATOR - IN 1/2" F - OUT 1/2" F - FLOW RATE 10 KG/H	€32.5 VAT EXCLUDED
00000000823	LOW PRESSURE REGULATOR - IN LEFT NUT CH 25 - OUT 1/2" F - FLOW RATE 10 KG/H	€35.0 VAT EXCLUDED

